

Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	3.5AH	
Dimensions	Length	134±2mm (5.28 inches)
	Width	67±1mm (2.64 inches)
	Container Height	60.5±1mm (2.38 inches)
	Total Height (with Terminal)	66.5±1mm (2.62 inches)
Approx Weight	Approx 1.35 kg (2.98lbs)	
Terminal	T1/T2	
Container Material	ABS	
Rated Capacity	3.50 AH/0.175A	(20hr , 1.80V/cell,25°C/77°F)
	3.26 AH/0.326A	(10hr, 1.80V/cell,25°C/77°F)
	2.965 AH/0.593A	(5hr, 1.75V/cell,25°C/77°F)
	2.604 AH/0.868A	(3hr, 1.75V/cell,25°C/77°F)
	2.18 AH/2.18A	(1hr, 1.60V/cell,25°C/77°F)
Max. Discharge Current	48.0A (5s)	
Internal Resistance	Approx 45mΩ	
Operating Temp.Range	Discharge	-15~50°C (5~122°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 1.05A. Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	General purpose batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	
Life expectancy	3~5 years at 25°C with charge voltage of 2.25V/cell	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Conform to:
IEC60896-21&22 and/or IEC61427

Constant Current Discharge (Amperes) at 25°C (77°F)




F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	6.67	4.43	3.65	3.21	2.63	2.05	1.70	1.04	0.786	0.647	0.549	0.475	0.378	0.316	0.173
1.80V/cell	7.98	5.31	4.30	3.68	2.94	2.25	1.84	1.12	0.840	0.688	0.577	0.496	0.392	0.326	0.175
1.75V/cell	9.58	6.09	4.77	4.06	3.15	2.41	1.95	1.17	0.868	0.704	0.593	0.510	0.403	0.334	0.177
1.70V/cell	11.1	6.80	5.26	4.40	3.36	2.53	2.03	1.21	0.890	0.721	0.606	0.522	0.409	0.339	0.180
1.65V/cell	12.2	7.37	5.64	4.71	3.54	2.64	2.10	1.25	0.915	0.739	0.620	0.531	0.415	0.343	0.182
1.60V/cell	13.5	7.98	6.06	4.98	3.72	2.75	2.18	1.28	0.937	0.758	0.633	0.544	0.424	0.349	0.183

Constant Power Discharge (Watts/cell) at 25°C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	12.4	8.29	6.87	6.06	5.00	3.94	3.28	2.03	1.53	1.26	1.08	0.935	0.746	0.625	0.343
1.80V/cell	14.4	9.73	7.95	6.88	5.55	4.29	3.53	2.16	1.63	1.34	1.13	0.972	0.772	0.643	0.346
1.75V/cell	17.1	11.0	8.75	7.53	5.90	4.57	3.72	2.24	1.68	1.37	1.15	0.996	0.790	0.658	0.349
1.70V/cell	19.6	12.2	9.55	8.10	6.25	4.76	3.86	2.32	1.72	1.39	1.18	1.02	0.802	0.668	0.355
1.65V/cell	21.3	13.0	10.1	8.59	6.54	4.94	3.98	2.38	1.75	1.42	1.20	1.03	0.813	0.675	0.360
1.60V/cell	23.1	13.9	10.7	8.92	6.79	5.10	4.11	2.43	1.79	1.46	1.22	1.05	0.828	0.686	0.361

Dimensions


T1 Terminal Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



- A** No supplementary charging required (Carry out supplementary charge before use if 100% capacity is required).
Supplementary charging required before use. Optional charging may be slow.
- B** 1. Charged for a above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
2. Charged for a above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
3. Charged for 8 ~10 hours at limited current 0.05 CA.
- C** Supplementary charging may often fail to recover the capacity. The battery should never be left standing until this is reached.